



### ART. A976BU+D377AU

#### 3 way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- Accessible shut-off valves and filters
- Flow rate: 8.7 gpm @ 60 psi (primary outlet)
- Flow rate: 7.4 gpm @ 60 psi (secondary outlet)
- Flow rate: 7.4 gpm @ 60 psi (third outlet)

To be used with thermostatic mixer A900BU+D400AU

Date \_\_\_\_\_

Project/Comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

#### Trim

- |  |              |
|--|--------------|
| <input type="checkbox"/> Chrome                  | 27 02 A976BU |
| <input type="checkbox"/> Matte Gun Metal PVD     | 27 P5 A976BU |
| <input type="checkbox"/> Matte British Gold PVD  | 27 P6 A976BU |
| <input type="checkbox"/> Matte Copper PVD        | 27 P9 A976BU |
| <br>   |              |
| <input type="checkbox"/> Brushed Stainless steel | 27 93 A976BU |

#### Rough

- |                          |              |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D377AU |
|--------------------------|--------------|

#### TOTAL PRICE

- |  |              |
|--|--------------|
| <input type="checkbox"/> Chrome                  | 27 02 A976BU |
| <input type="checkbox"/> Matte Gun Metal PVD     | 27 P5 A976BU |
| <input type="checkbox"/> Matte British Gold PVD  | 27 P6 A976BU |
| <input type="checkbox"/> Matte Copper PVD        | 27 P9 A976BU |
| <br>   |              |
| <input type="checkbox"/> Brushed Stainless steel | 27 93 A976BU |

## ART. A976BU+D377AU

3 way diverter with integrated volume control

